

HARMAN

FAX COVER SHEET



This fax is from the following department:

- Accounting
- Advertising
- Co-Op
- HR
- Research & Development

To: Bill Sendelback From: HARMAN'S (Lamy Gross)

Sending to fax #: 972-560-2258 Date: 7-28-04 # of pgs: 4

Please call if you do not receive all pages.

Message:

FYI

cc sent to: Brian Zeigler




*352 Mountain House Road
Halifax, PA 17032
Phone: (717) 362-9080
Fax: (717) 362-4251
E-mail: sales@harmanstoves.com*

July 2004

Notice To Stove Installers:

Harman Stove Company is happy to announce that effective immediately the Selkirk Direct-Temp TM is approved to be used on any Harman direct vent gas hearth appliance, with a coaxial venting system.


Dane P. Harman, President



352 Mountain House Road
Halifax, PA 17032
Phone: (717) 362-9080
Fax: (717) 362-4251
E-mail: sales@harmanstoves.com

INSTALLATION INSTRUCTION APPENDIX FOR
HARMAN STOVE COMPANY MODELS:

Harman Clarity, Harman Conquest, and HB-38 (Harman-Built Fireplace).
Also on any Harman direct vent gas hearth appliance with a coaxial vent system.

Selkirk Model Direct-Temp TM direct venting system has now been added as an approved venting option by our safety certification organization, Intertek Testing Services/Warnock Hersey, for the above referenced direct vent gas appliances.

When using Selkirk Direct-Temp TM as an alternative venting system, follow the same system layout, clearance to combustibles and other guidelines as currently included in our main installation instructions for the above referenced appliances. The Selkirk Direct-Temp TM installation instructions are included with all Selkirk Direct-Temp TM terminations and provide clarification on how certain parts/pieces are assembled, but do not give specifics on system layout options. Follow both sets of instructions.

Attached is a cross-reference chart for the Selkirk Direct-Temp TM system versus the system currently referenced in our instructions.

If any questions arise with respect to correlating parts or issues associated with the Selkirk Direct-Temp TM system, contact Selkirk Technical Support at 800-848-2149, ext 203 or our Harman Technical Support at 717-362-1422.

Effective Date: July 2004

Authorized by: Dane P. Harman
Dane P. Harman, President
Harman Stove Company

CROSS REFERENCE CHART

Selkirk Direct-Temp™		Simpson Dura-Vent Direct Vent GS®	
Stock No.	Description	Stock No.	Description
4DT-6	6" Pipe Length, Galvanized	908	6" Pipe Length, Galvanized
4DT-6B	6" Pipe Length, Black	908B	6" Pipe Length, Black
4DT-9	9" Pipe Length, Galvanized	907	9" Pipe Length, Galvanized
4DT-9B	9" Pipe Length, Black	907B	9" Pipe Length, Black
4DT-12	12" Pipe Length, Galvanized	906	12" Pipe Length, Galvanized
4DT-12B	12" Pipe Length, Black	906B	12" Pipe Length, Black
4DT-18	18" Pipe Length, Galvanized	n/a	n/a
4DT-18B	18" Pipe Length, Black	n/a	n/a
4DT-24	24" Pipe Length, Galvanized	904	24" Pipe Length, Galvanized
4DT-24B	24" Pipe Length, Black	904B	24" Pipe Length, Black
4DT-36	36" Pipe Length, Galvanized	903	36" Pipe Length, Galvanized
4DT-36B	36" Pipe Length, Black	903B	36" Pipe Length, Black
4DT-48	48" Pipe Length, Galvanized	902	48" Pipe Length, Galvanized
4DT-48B	48" Pipe Length, Black	902B	48" Pipe Length, Black
4DT-AJ	Adjustable Length, 11"-14", Galv.	911	Adjustable Length, 11"-14", Galv.
4DT-AJB	Adjustable Length, 11"-14", Black	911B	Adjustable Length, 11"-14", Black
4DT-EL45	45° Elbow, Galvanized	945	45° Elbow, Galvanized
4DT-EL45B	45° Elbow, Black	945B	45° Elbow, Black
4DT-EL90	90° Elbow, Galvanized	990	90° Elbow, Galvanized
4DT-EL90B	90° Elbow, Black	990B	90° Elbow, Black
4DT-AA	Appliance Adaptor, Black	n/a	n/a
4DT-RD	Restriction Disc	929	Restrictor Disc
4DT-CS	Ceiling Support	949	Round Ceiling Support / Wall Thimble Cover
4DT-CSS	Cathedral Support Box	941	Cathedral Ceiling Support Box
4DT-WS/B	Wall Support/Band	988	Wall Stap
4DT-OS	Offset Support	989	Elbow Strap
4DT-WT	Round Wall Thimble, Black	942	Wall Thimble
4DT-FS	Firestop Spacer	963	Ceiling Firestop
4DT-TP	Trim Plate, Black	n/a	n/a
4DT-HKA	Horizontal Term. Kit A	970	Basic Horizontal Term. Kit
4DT-HKB	Horizontal Term. Kit B	971	Horizontal Termination Kit A
4DT-VKC	Vertical Termination Kit	978	Vertical Termination Kit
4DT-HVC	High Wind Vertical Cap	991	High Wind Termination Cap
4DT-HHC	High Wind Horizontal Cap	985	Horiz. Square High Wind Termination
4DT-SC	Storm Collar	953	Storm Collar
4DT-AF6	Adjustable Flashing, 0/12-6/12	943	Adj. Roof Flashing 0/12-6/12
4DT-AF12	Adjustable Flashing, 6/12-12/12	943S	Steep Roof Flash. 7/12-12/12
4DT-VS	Vinyl Siding Standoff	950	Vinyl Siding Standoff
4DT-VSP	Vinyl Siding Shield Plate	n/a	n/a
4DT-ST14	Snorkel Termination 14"	982	Snorkel Termination Cap 14"
4DT-ST36	Snorkel Termination 36"	981	Snorkel Termination Cap 36"